

DESCRIPTION

Elevation[™] SP1 Hi-Tack Primer is a water-based, pressure sensitive primer intended for use with various types of self-adhesive membranes including modified bitumen and TPO. SP1 is suitable for application to concrete, plywood and polyisocyanurate roofing insulation. VOC compliant in all of North America.



SP1 Hi-Tack Primer is manufactured from strong, elastic, low Tg polymer resin and special additives in a water vehicle. SP1 exhibits permanent surface tack.

SPECIFICATIONS

SP1 SPECIFICATION

Viscosity	ASTM D 2196	500 cps
Solids by Weight	ASTM D 1644	45%
Solids by Volume	ASTM D 2697	44%
Weight Per Gallon	ASTM D 1147	8.5 lbs.
Flash Point	ASTM D 56	NA
VOC	EPA 24	<5 g/l

COLOR

White/Dries Clear

PACKAGING

Container Size: 5 gallon pails

INSTALLATION

The surface must be clean and dry. Temperature must be a minimum of 40°F with humidity of less than 90% for proper curing. Apply SP1 at the rate of one quarter to one half gallon per 100 square feet. Porous surfaces will require more adhesive. Greater application rates will extend the primer's cure time. The product should be applied with a 1/2 inch nap roller or suitable spray equipment. Allow the adhesive to dry completely. The color of the primer will change from white to a clear when the primer is fully dry.

Shelf Life: Two years from the date of manufacture.

CAUTION: Avoid prolonged contact with skin or fumes. If irritation occurs seek medical attention. Keep out of reach of children. Read SDS prior to use.